



### Main

|                           |   |
|---------------------------|---|
| Range                     | PowerLogic  |
| Product or component type | I/O module  |
| Device application        | Optional expansion module                                     |
| Range compatibility       | PowerLogic PM8000<br>PowerLogic ION7400<br>PowerLogic ION9000 |

### Complementary

|                   |  |
|-------------------|--|
| Number of outputs | 2 analog, 0-20 mA or 4-20 mA or 0...10 V |
| Number of inputs  | 4 analog 0...20 mA/4...20 mA 0...30 V    |
| Width             | 22 mm                                    |
| Depth             | 90.5 mm                                  |
| Height            | 90.5 mm                                  |
| Net weight        | 140 g                                    |

### Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| Ambient air temperature for operation | -25...70 °C                  |
| Ambient air temperature for storage   | -40...85 °C                  |
| IP degree of protection               | IP30 conforming to IEC 60529 |

### Offer Sustainability

|                   |   |
|-------------------|---|
| EU RoHS Directive | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| WEEE              | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications